

Gasket Cleaner Spray**GÜVENLİK BİLGİ FORMU**

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Reference number: EYS F 831-1-22
Revision date: 5/26/2021 Issue date: 11/16/2018 Version: 3.0**SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING****1.1. Product identifier**

Product form : Mixture
Trade name : Skala Gasket Cleaner Spray
Product code : 250233
Vaporizer : Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against**1.2.1. Relevant identified uses**

Use of the substance/mixture : Cleansing product

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Manufacturer

Üretici Firma	SKALA KİMYA SAN VE TİC. A.Ş.
Adres	Akşemsettin Mh. Fatih Bulvarı Serap Sk. No:5/A Sultanbeyli/İSTANBUL
Telefon	0850 969 19 05
İlgili Kişi	Süleyman KARAKAYA

1.4. Emergency telephone number

Emergency number : 0850 969 19 05

SECTION 2: HAZARDS IDENTIFICATION**2.1. Classification of the substance or mixture**

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 2	H223;H229
Acute toxicity (dermal), Category 4	H312
Acute toxicity (inhalation:vapour) Category 4	H332
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 1	H318
Reproductive toxicity, Category 2	H361
Specific target organ toxicity —Single exposure, Category 3,	H336

Gasket Cleaner Spray**GÜVENLİK BİLGİ FORMU**

Narcosis

Specific target organ toxicity —Repeated exposure, Category 2 H373

Hazardous to the aquatic environment — Chronic Hazard, Category 3 H412

Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Flammable aerosol. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure. May cause drowsiness or dizziness. Harmful in contact with skin. Harmful if inhaled. Causes skin irritation. Causes serious eye damage. Harmful to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]



Hazard pictograms (CLP) :

GHS02 GHS05 GHS07 GHS08

Signal word (CLP) : Danger

Hazardous ingredients : propan-2-ol; isopropyl alcohol; isopropanol; Naphtha (petroleum), hydrotreated light*; xylene; ethylbenzene; 2-butoxyethanol; ethyleneglycol monobutyl ether; butyl cellosolve; benzenesulfonic acid, 4-C10-13-sec-alkyl derivs.

Hazard statements (CLP) : H223 - Flammable aerosol.
H229 - Pressurised container: May burst if heated.
H312+H332 - Harmful in contact with skin or if inhaled
H315 - Causes skin irritation.
H318 - Causes serious eye damage.
H336 - May cause drowsiness or dizziness.
H361 - Suspected of damaging fertility or the unborn child.
H373 - May cause damage to organs through prolonged or repeated exposure.
H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP): P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 - Do not spray on an open flame or other ignition source.
P251 - Do not pierce or burn, even after use.
P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P305+P351+P338+P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
P321 - Specific treatment (see supplemental first aid instruction on this label).

Gasket Cleaner Spray
GÜVENLİK BİLGİ FORMU
2.3. Other hazards

No additional information available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS
3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
xylene substance with a Community workplace exposure limit (Note C)	(CAS-No.) 1330-20-7 (EC-No.) 215-535-7 (EC Index-No.) 601-022-00-9	$\geq 40 - < 45$	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Dermal), H312 Skin Irrit. 2, H315
Naphtha (petroleum), hydrotreated light* (Note P)	(CAS-No.) 64742-49-0 (EC-No.) 265-151-9 (EC Index-No.) 649-328-00-1	$\geq 13 - < 16$	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361f STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
2-butoxyethanol; ethyleneglycol monobutyl ether; butyl cellosolve substance with a Community workplace exposure limit	(CAS-No.) 111-76-2 (EC-No.) 203-905-0 (EC Index-No.) 603-014-00-0 (REACH-no) 01-2119475108-36	$\geq 13 - < 16$	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319

Gasket Cleaner Spray
GÜVENLİK BİLGİ FORMU

ethylbenzene substance with a Community workplace exposure limit	(CAS-No.) 100-41-4 (EC-No.) 202-849-4 (EC Index-No.) 601-023-00-4	$\geq 10 - < 13$	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:vapour), H332 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
propan-2-ol; isopropyl alcohol; isopropanol	(CAS-No.) 67-63-0 (EC-No.) 200-661-7 (EC Index-No.) 603-117-00-0	$\geq 8 - < 9$	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Carbondioxide	(CAS-No.) 124-38-9 (EC-No.) 204-696-9	$\geq 3 - < 4$	Press. Gas (Comp.), H280
benzenesulfonic acid, 4-C10-13-sec-alkyl derivs.	(CAS-No.) 85536-14-7 (EC-No.) 287-494-3	$\geq 3 - < 4$	Acute Tox. 4 (Oral), H302 Skin Corr. 1, H314 Aquatic Chronic 3, H412
Alcohols, C10-16, ethoxylated, sulfates, sodium salts	(CAS-No.) 68585-34-2	$\geq 2 - < 3$	Skin Irrit. 2, H315 Eye Irrit. 2, H319

Note C : Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Note P : The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7). WHEN THE SUBSTANCE IS NOT CLASSIFIED AS A CARCINOGEN AT LEAST THE PRECAUTIONARY STATEMENTS (P102-)P260-P262- P301 + P310-P331 (TABLE 3.1) OR THE S-PHRASES (2-)23-24-62 (TABLE 3.2) SHALL APPLY. THIS NOTE APPLIES ONLY TO CERTAIN COMPLEX OIL-DERIVED SUBSTANCES IN PART 3.

Full text of H-statements: see section 16

SECTION 4: FIRST AID MEASURES
4.1. Description of first aid measures

- First-aid measures general* : *IF exposed or concerned: Get medical advice/attention. Call a poison center or a doctor if you feel unwell.*
- First-aid measures after inhalation* : *Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.*
- First-aid measures after skin contact* : *Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.*
- First-aid measures after eye contact* : *Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.*
- First-aid measures after ingestion* : *Call a poison center or a doctor if you feel unwell.*

Gasket Cleaner Spray**GÜVENLİK BİLGİ FORMU****4.2. Most important symptoms and effects, both acute and delayed**

Symptoms/effects : *May cause drowsiness or dizziness.*
Symptoms/effects after skin contact : *Irritation.*
Symptoms/effects after eye contact : *Serious damage to eyes.*

**4.3. Indication of any immediate medical attention and special treatment needed
Treat symptomatically.****SECTION 5: FIREFIGHTING MEASURES****5.1. Extinguishing media**

Suitable extinguishing media : *Water spray. Dry powder. Foam. Carbon dioxide.*

5.2. Special hazards arising from the substance or mixture

Fire hazard : *Flammable aerosol.*
Explosion hazard : *Pressurised container: May burst if heated.*
Hazardous decomposition products in case of fire : *Toxic fumes may be released.*

5.3. Advice for firefighters

Protection during firefighting : *Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.*

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1. Personal precautions, protective equipment and emergency procedures****6.1.1. For non-emergency personnel**

Emergency procedures : *Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin, eyes and clothing.*

6.1.2. For emergency responders

Protective equipment : *Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".*

6.2. Environmental precautions

Avoid release to the environment.

Gasket Cleaner Spray

GÜVENLİK BİLGİ FORMU

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up* : *Mechanically recover the product. Notify authorities if product enters sewers or public waters.*
Other information : *Dispose of materials or solid residues at an authorized site.*

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

- Precautions for safe handling* : *Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Do not breathe dust/ fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Do not get in eyes, on skin, or on clothing.*
Hygiene measures : *Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.*

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions* : *Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.*

7.3. Specific end use(s)

No additional information available

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Carbondioxide (124-38-9)		
EU	Local name	Carbon dioxide
EU	IOEL TWA	9000 mg/m ³
EU	IOEL TWA [ppm]	5000 ppm
EU	Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC

xylene (1330-20-7)		
EU	Local name	Xylene, mixed isomers, pure
EU	IOEL TWA	221 mg/m ³
EU	IOEL TWA [ppm]	50 ppm
EU	IOEL STEL	442 mg/m ³

Gasket Cleaner Spray
GÜVENLİK BİLGİ FORMU

EU	IOEL STEL [ppm]	100 ppm
EU	Notes	Skin
EU	Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC

ethylbenzene (100-41-4)		
EU	Local name	Ethylbenzene
EU	IOEL TWA	442 mg/m ³
EU	IOEL TWA [ppm]	100 ppm
EU	IOEL STEL	884 mg/m ³
EU	IOEL STEL [ppm]	200 ppm
EU	Notes	Skin
EU	Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
United Kingdom	WEL TWA (OEL TWA) [1]	441 mg/m ³
United Kingdom	WEL TWA (OEL TWA) [2]	100 ppm
United Kingdom	WEL STEL (OEL STEL)	552 mg/m ³
United Kingdom	WEL STEL (OEL STEL) [ppm]	125 ppm

2-butoxyethanol; ethyleneglycol monobutyl ether; butyl cellosolve (111-76-2)		
EU	Local name	2-Butoxyethanol
EU	IOEL TWA	98 mg/m ³
EU	IOEL TWA [ppm]	20 ppm
EU	IOEL STEL	246 mg/m ³
EU	IOEL STEL [ppm]	50 ppm
EU	Notes	Skin
EU	Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
United Kingdom	WEL TWA (OEL TWA) [1]	123 mg/m ³
United Kingdom	WEL TWA (OEL TWA) [2]	25 ppm
United Kingdom	WEL STEL (OEL STEL)	246 mg/m ³

2-butoxyethanol; ethyleneglycol monobutyl ether; butyl cellosolve (111-76-2)		
United Kingdom	WEL STEL (OEL STEL) [ppm]	50 ppm

8.2. Exposure controls

Appropriate engineering controls:
 Ensure good ventilation of the work station.

Hand protection:
 Protective gloves

Eye protection:
 Safety glasses

Skin and body protection:

Gasket Cleaner Spray**GÜVENLİK BİLGİ FORMU**

Wear suitable protective clothing

Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

Personal protective equipment symbol(s):



Environmental exposure controls:

Avoid release to the environment.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**9.1. Information on basic physical and chemical properties**

Physical state	: Liquid
Appearance	: liqued under pressure.
Colour	: No data available
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Flammable aerosol.
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/ water (Log Pow)	: No data available
Viscosity, kinematic	: No data available

Gasket Cleaner Spray

GÜVENLİK BİLGİ FORMU

Viscosity, dynamic	: No data available
Explosive properties	: Pressurised container: May burst if heated.
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

Flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Harmful in contact with skin.
Acute toxicity (inhalation)	: Harmful if inhaled.

ATE CLP (dermal)	1963.234 mg/kg bodyweight
ATE CLP (vapours)	17.612 mg/L/4h

Naphtha (petroleum), hydrotreated light* (64742-49-0)	
LD50 oral rat	≥ 5 g/kg
LD50 dermal rabbit	≥ 2 g/kg
LC50 Inhalation - Rat	≥ 5.2 mg/L

xylene (1330-20-7)	
LD50 dermal rabbit	12126 mg/kg bodyweight Animal: rabbit, Animal sex: male

ethylbenzene (100-41-4)	
LD50 oral rat	3500 mg/kg (Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	15432 mg/kg bodyweight (24 h, Rabbit, Male, Experimental value, Dermal)
LC50 Inhalation - Rat	17.8 mg/L (4 h, Rat, Male, Experimental value, Inhalation (vapours))

Gasket Cleaner Spray

GÜVENLİK BİLGİ FORMU

2-butoxyethanol; ethyleneglycol monobutyl ether; butyl cellosolve (111-76-2)	
LD50 oral rat	1746 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Male, Experimental value, Oral)
LD50 oral	1414 mg/kg bodyweight (OECD 401: Acute Oral Toxicity, Guinea pig, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg bodyweight (OECD 402: Acute Dermal Toxicity, Rat, Male / female, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat [ppm]	450 ppm (Equivalent or similar to OECD 403, 4 h, Rat, Female, Experimental value, Inhalation (vapours))

benzenesulfonic acid, 4-C10-13-sec-alkyl derivs. (85536-14-7)

<i>benzenesulfonic acid, 4-C10-13-sec-alkyl derivs. (85536-14-7)</i>	
LD50 oral rat	1470 mg/kg bodyweight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg bodyweight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.

STOT-single exposure	: May cause drowsiness or dizziness.
STOT-repeated exposure	: May cause damage to organs through prolonged or repeated exposure.

<i>Naphtha (petroleum), hydrotreated light* (64742-49-0)</i>	
LOAEC (inhalation, rat, vapour, 90 days)	4.71 mg/l air Animal: rat, Guideline: EU Method B.29 (Sub-Chronic Inhalation Toxicity:90-Day Study)
NOAEC (inhalation, rat, vapour, 90 days)	2.355 mg/l air Animal: rat, Guideline: EU Method B.29 (Sub-Chronic Inhalation Toxicity:90-Day Study)
xylene (1330-20-7)	
LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)
ethylbenzene (100-41-4)	
NOAEL (oral, rat, 90 days)	75 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

Aspiration hazard	: Not classified
-------------------	------------------

Gasket Cleaner Spray
GÜVENLİK BİLGİ FORMU

Skala Gasket Cleaner Spray	
Vaporizer	Aerosol

SECTION 12: ECOLOGICAL INFORMATION
12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.

<i>xylene (1330-20-7)</i>	
LC50 - Fish [1]	2.6 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	> 3.4 mg/l Test organisms (species): Ceriodaphnia dubia
NOEC chronic fish	> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'

<i>ethylbenzene (100-41-4)</i>	
LC50 - Fish [1]	5.1 mg/l (ASTM, 96 h, Menidia menidia, Flow-through system, Salt water, Experimental value, Lethal)
EC50 - Crustacea [1]	1.8 – 2.4 mg/l (US EPA, 48 h, Daphnia magna, Static system, Fresh water, Experimental value)
EC50 72h - Algae [1]	5.4 mg/l (US EPA, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Cell numbers)
EC50 72h - Algae [2]	5.4 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	7.7 mg/l Test organisms (species): Skeletonema costatum
EC50 96h - Algae [2]	3.6 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
LOEC (chronic)	1.7 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC (chronic)	0.96 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'

<i>2-butoxyethanol; ethyleneglycol monobutyl ether; butyl cellosolve (111-76-2)</i>	
LC50 - Fish [1]	1474 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 - Crustacea [1]	1550 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 72h - Algae [1]	911 mg/l (OECD 201: Alga, Growth Inhibition Test, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)

benzenesulfonic acid, 4-C10-13-sec-alkyl derivs. (85536-14-7)

Gasket Cleaner Spray
GÜVENLİK BİLGİ FORMU

<i>benzenesulfonic acid, 4-C10-13-sec-alkyl derivs. (85536-14-7)</i>	
LC50 - Fish [1]	1.67 mg/l (US EPA, 96 h, Lepomis macrochirus, Static system, Fresh water, Experimental value)
EC50 - Crustacea [1]	2.9 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Read-across, GLP)
ErC50 algae	127.9 mg/l (72 h, Desmodesmus subspicatus, Static system, Read-across, GLP)

12.2. Persistence and degradability

ethylbenzene (100-41-4)	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.44 g O ₂ /g substance
Chemical oxygen demand (COD)	2.1 g O ₂ /g substance
ThOD	3.17 g O ₂ /g substance
2-butoxyethanol; ethyleneglycol monobutyl ether; butyl cellosolve (111-76-2)	
Persistence and degradability	Readily biodegradable in water.
benzenesulfonic acid, 4-C10-13-sec-alkyl derivs. (85536-14-7)	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.

12.3. Bioaccumulative potential

ethylbenzene (100-41-4)	
BCF - Fish [1]	1 (6 week(s), Oncorhynchus kisutch, Flow-through system, Salt water, Experimental value)
Partition coefficient n-octanol/water (Log Pow)	3.6 (Experimental value, EU Method A.8: Partition Coefficient, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
2-butoxyethanol; ethyleneglycol monobutyl ether; butyl cellosolve (111-76-2)	
Partition coefficient n-octanol/water (Log Pow)	0.81 (Test data, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
benzenesulfonic acid, 4-C10-13-sec-alkyl derivs. (85536-14-7)	
BCF - Other aquatic organisms [1]	159 (11.5 day(s), Palaemonetes sp., Flow-through system, Salt water, Experimental value, Fresh weight)
benzenesulfonic acid, 4-C10-13-sec-alkyl derivs. (85536-14-7)	
Partition coefficient n-octanol/water (Log Pow)	2.2 (Experimental value, OECD 123: Partition Coefficient (1-Octanol/Water): Slow-Stirring Method, 23 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

Gasket Cleaner Spray

GÜVENLİK BİLGİ FORMU

12.4. Mobility in soil

ethylbenzene (100-41-4)	
Surface tension	71.2 mN/m (23 °C, 0.058 g/l, EU Method A.5: Surface tension)
Partition coefficient n-octanol/water (Log Koc)	2.71 (log Koc, PCKOCWIN v1.66, QSAR)
Ecology - soil	Low potential for adsorption in soil. Toxic to soil organisms.
2-butoxyethanol; ethyleneglycol monobutyl ether; butyl cellosolve (111-76-2)	
Surface tension	65.03 mN/m (20 °C, 2 g/l)
Ecology - soil	Low potential for adsorption in soil.
benzenesulfonic acid, 4-C10-13-sec-alkyl derivs. (85536-14-7)	
Surface tension	35.4 mN/m (20 °C, EU Method A.5: Surface tension)
Ecology - soil	Adsorbs into the soil.

12.5. Results of PBT and vPvB assessment

Component	
2-butoxyethanol; ethyleneglycol monobutyl ether; butyl cellosolve (111-76-2)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
ethylbenzene (100-41-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
benzenesulfonic acid, 4-C10-13-sec-alkyl derivs. (85536-14-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Other adverse effects

No additional information available

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Regional legislation (waste)	:	Disposal must be done according to official regulations.
Waste treatment methods	:	Dispose of contents/container in accordance with licensed collector's sorting instructions.
Ecology - waste materials	:	Avoid release to the environment.
European List of Waste (LoW) code	:	14 06 03* - other solvents and solvent mixtures 1501 11* - metallic packaging containing a dangerous solid porous matrix (e.g. asbestos), including empty pressure containers
R code/ D code	:	R13 - Storage of waste pending any of the operations numbered R 1 to R 12 (excluding temporary storage, pending collection, on the site where the waste is produced)

Gasket Cleaner Spray
GÜVENLİK BİLGİ FORMU
SECTION 14: TRANSPORT INFORMATION

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
1950	1950	1950	1950	1950
14.2. UN proper shipping name				
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS
Transport document description				
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1	UN 1950 AEROSOLS, 2.1	UN 1950 AEROSOLS, 2.1
14.3. Transport hazard class(es)				
2.1	2.1	2.1	2.1	2.1
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No
No supplementary information available				

14.6. Special precautions for user**- Overland transport**

Classification code (ADR)	: 5F
Special provisions (ADR)	: 190, 327, 344, 625
Limited quantities (ADR)	: 1l
Excepted quantities (ADR)	: E0
Packing instructions (ADR)	: P207
Special packing provisions (ADR)	: PP87, RR6, L2
Mixed packing provisions (ADR)	: MP9
Transport category (ADR)	: 2
Special provisions for carriage - Packages (ADR)	: V14
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV9, CV12
Special provisions for carriage - Operation (ADR)	: S2
Tunnel restriction code (ADR)	: D

- Transport by sea

Special provisions (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Packing instructions (IMDG)	: P207, LP200
Special packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D
EmS-No. (Spillage)	: S-U
Stowage category (IMDG)	: None
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69

- Air transport

PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

- Inland waterway transport

Classification code (ADN)	: 5F
Special provisions (ADN)	: 190, 327, 344, 625
Limited quantities (ADN)	: 1L

Gasket Cleaner Spray
GÜVENLİK BİLGİ FORMU

Excepted quantities (ADN) : E0
Equipment required (ADN) : PP, EX, A
Ventilation (ADN) : VE01, VE04
Number of blue cones/lights (ADN) : 1

- Rail transport

Special provisions (RID) : 190, 327, 344, 625
Limited quantities (RID) : 1L
Excepted quantities (RID) : E0
Packing instructions (RID) : P207, LP200
Special packing provisions (RID) : PP87, RR6, L2
Mixed packing provisions (RID) : MP9
Transport category (RID) : 2
Special provisions for carriage –
Packages (RID) : W14
Special provisions for carriage -
Loading, unloading and handling
(RID) : CW9, CW12
Colis express (express parcels) (RID) : CE2
Hazard identification number (RID) : 23

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: REGULATORY INFORMATION
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:

3(a) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F	Skala Gasket Cleaner Spray-SDS ; propan-2-ol; isopropyl alcohol; isopropanol ; Naphtha (petroleum), hydrotreated light* ; xylene ; ethylbenzene
3(b) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10	Skala Gasket Cleaner Spray-SDS ; propan-2-ol; isopropyl alcohol; isopropanol ; Naphtha (petroleum), hydrotreated light* ; xylene ; ethylbenzene ; 2-butoxyethanol; ethyleneglycol monobutyl ether; butyl cellosolve
3(c) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1	Skala Gasket Cleaner Spray-SDS ; Naphtha (petroleum), hydrotreated light*

Gasket Cleaner Spray
GÜVENLİK BİLGİ FORMU

40. Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.

propan-2-ol; isopropyl alcohol; isopropanol ; Naphtha (petroleum), hydrotreated light* ; xylene ; ethylbenzene

Contains no substance on the REACH candidate list Contains no REACH Annex XIV substances

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: OTHER INFORMATION

Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration

Gasket Cleaner Spray
GÜVENLİK BİLGİ FORMU

OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006. Classification according to Regulation (EC) No. 1272/2008 [CLP].
 Classification according to Classification, Labelling and Packaging of Substances and Mixtures (SEA) Regulation published in the Official Journal numbered 28848 on December 11, 2013.

Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aerosol 2	Aerosol, Category 2
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Press. Gas (Comp.)	Gases under pressure : Compressed gas
Repr. 2	Reproductive toxicity, Category 2
Repr. 2	Reproductive toxicity, Category 2
Skin Corr. 1	Skin corrosion/irritation, Category 1
Skin Irrit. 2	Skin corrosion/irritation, Category 2

Gasket Cleaner Spray
GÜVENLİK BİLGİ FORMU

ST0T RE 2	Specific target organ toxicity — Repeated exposure, Category 2
ST0T SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H223	Flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H361	Suspected of damaging fertility or the unborn child.
H361f	Suspected of damaging fertility.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Disclaimer: This Certificate provides restrictions for use of the specified product based only on those materials restricted by IFRA Standards for the toxicity endpoint(s) described in each Standard. This Certificate does not provide certification of a comprehensive safety assessment of all product constituents.

SDS_EU_SEL_TAER

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable

